

## care instructions

pflegeanleitung · notice d'entretien · onderhoudvoorschrift

Before installation, please read this installation and maintenance manual thoroughly and keep it for future reference.  
Any damage caused by improper use is not covered by our guarantee and we cannot accept any liability.

### Maintenance instructions:

Please observe the following maintenance instructions, so that you can enjoy your high quality EMCO products for as long as possible.

**Glass surfaces:** Please wipe with a damp chamois. Simply wipe the glass edges dry. After cleaning, it is important that all surfaces are wiped dry with a soft, lint-free cloth.

**Mineral cast:** A clean, soft damp cloth is all you need for cleaning (**no microfibre cloths!**). If there is a lot of dirt, use a mild liquid detergent (without any alcohol or scouring creams) and warm water. Please make sure that the water temperature does not exceed 65 °C. Any spills should be cleaned away immediately. To maintain the lustre of the mineral cast surface, we recommend that from time to time you apply a high-quality car polish and repolish it.

### Intended use

The emcobad washbasins, boards and modules have been manufactured for use in bathrooms and, in the commercial sector, for the storage of commercial bathroom accessories. They are intended solely for this purpose. Any other use is considered to be improper and may lead to damage or even personal injury. Parents must ensure that their children never use the bathroom unattended and do not use it as a play area, since the use of electrical appliances and water can lead to damage or even personal injury. Improper use includes overfilling and overloading the washbasins and also sitting, climbing and standing on them.

**We cannot accept liability for any damage caused by improper use.**

### Information for daily use

To make sure your washbasin lasts a long time, please note the following information regarding its daily use:

1. Protect the high-quality cast mineral and glass surfaces from excessive exposure to light and from heavy, sharp, abrasive, hot, corrosive or acidic objects. These may result in unsightly discolouration, dents, edges or scratches. Over the years, slight colour variations are unavoidable with all materials.
2. Remove any dirt as soon as possible with a soft damp cloth and lukewarm water. Often no cleaning agents are required.  
Then wipe dry.
3. Spilled corrosive substances must be removed immediately. Do not allow them to penetrate!
4. Do not use abrasive cleaners that contain alcohol or scouring creams, or any microfibre cloths.
5. The water temperature on the mineral cast surface should not exceed 65 degrees.